



## DERALUNOX

### ALUMINIUM AND STAINLESS DEOXIDIZER

#### » Features

Clear liquid of acid chemical reaction.

#### » Properties

**DERALUNOX** is miscible in water in all proportions, has a low surface tension, ensures a perfect penetration in encrusted dirtiness.

**DERALUNOX** solubilizes calcified deposits and the fixed metal oxide on the aluminium surfaces and certain stainless steels.

#### » Utilization

**DERALUNOX** is used for renovation and descaling of rolling equipment, such as road and rail cisterns, fixed tanks, cleaning and renewal of containers.


**DERALUNOX** is used in transport companies, agro-food, highways, factories, ports, shipyards, etc. ...

**DERALUNOX** descales and renews the rims of rolling equipment particularly oxidized.

With **DERALUNOX** you will get a renewed surface with a shiny appearance.

#### » Cautions

Keep out of children reach. Close the package after use. Avoid contact with the epidermis. In case of contact with skin or eyes, rinse with plenty of water. Do not mix with other products. Use appropriate protective material. Protect from freezing. Do not use on anodized aluminum, light alloys, galvanized, etc ... Always carry out a test to determine compatibility and appropriate contact time. Chemical Product: Always read the label before using.



#### » Application

Wet slightly and uniformly the surfaces to be cleaned.

Apply **DERALUNOX** diluted with cold water with a concentration in accordance with the thickness of the dirt to be cleaned, usually a dilution range from 1 litre per 2 to 3 litres of water for descaling operations or renewal, and 1 litre to 8 to 10 litres of water for frequent cleaning.

**DERALUNOX** is applied by spraying or brushing always from top to bottom.

Allow to react for 5 minutes and then wash with water, preferably under pressure always from top to bottom.

**DERALUNOX** is a product of acid character, in the case of exterior cleaning materials transportation or agri-food industry after the final cleaning and until neutralization of surfaces, the operation is finished by washing with a detergent compatible with food industry followed by a washing with potable water.

**DERALUNOX** can be applied by immersion or bathing. For renewal and deoxidation of small pieces dilute at the proportion of 1 liter to 5 liters of water depending on the nature of dirtiness or oxidation (5-15 minutes).

