



## LUBRI-F6

MULTIPURPOSE HIGH PERFORMANCE LUBRICANT

» **Lubri-F6** is a neutral product, colourless, non-irritating, UV resistant and with a pleasant pine odour. Contains no silicone or chlorinated solvents.

**Lubri-F6** is an excellent multipurpose lubricant that through its low surface tension penetrates easily in incrustated oxides.

The anti-moisture characteristics of **LUBRI-F6** make possible its application in extreme conditions. Can be used in emergencies to prevent humidity or applied in a preventive way.

**Lubri-F6** has a dielectric capacity of 63 000 Volt tested according to IEC 156 Standard.

### » Utilization

**Lubri-F6** has an excellent performance to loosen metal pieces blocked by corrosion or oxidation, such as nuts, screws, bolts, hinges, joints, rails, joints, axles and other calcined mechanisms. Eliminates charred dirt and heavy and light hydrocarbons. It is compatible with all types of plastics, rubbers and does not attack paintings. When applied to metals, leaves a anticorrosion film.

**Lubri-F6** is also used in all lubrication applications. Can be used in tools, machines, rails, hinges, etc..., as well as in all kinds of places where the micro-lubrication is essential.

**Lubri-F6** is an excellent multipurpose product for all types of industrial maintenance tasks.

### » Application

Shake well before using. Spray Lubri-F6 in calcined pieces, let soak a few seconds for that penetration be effective. Repeat if needed.



## 6 Functions:

- *Lubricant*
- *Deblock*
- *Deoxidising*
- *Protective anti-corrosion*
- *Degreaser*
- *Anti-humidity dielectric*

### » Cautions

Keep out of children reach. Avoid contact with eyes. Contents under pressure, do not expose to temperatures exceeding 50°C. Do not puncture or incinerate even when empty. Do not spray on incandescent material. Always carry out a test in order to determine the compatibility and the contact time. Chemical product: Always read the label before using.

